

WHEEL DOLLY



INTENDED USE

For removal and installation of single and dual wheels on raised buses and trucks. Ideal for brake work.

SPECIFICATIONS

Lifting speed:

- 52 inches per minutes.

Lifting fork tilt adjustment:

- 10 degrees above horizontal.
- 4 degrees below horizontal.

Operating air pressure:

- 100 to 120 PSI.

Wheel diameter:

- 5 inches with ball bearings.



FEATURES

- Ergonomic design promotes health and safety in the work place.
- Open centre design allows full access to the wheel mounting hardware.
- Heavy capacity ; 1000 lbs.
- Fast and easy operation, thanks to the air driven hydraulic pump.
- Lifting fork tilts up to 10 degrees and down 4 degrees, in order to match the wheel to the wheel axle.
- For precise control, a hand pump operates the tilt on the lifting forks.
- Handling is made easy by means of two full length handles.
- Heavy duty ball bearing wheels.
- Safety cam-buckle strap provided to secure tires and wheels to the dolly.
- Counterbalanced version is available to use with parallelogram lifts.

Manufactured by:



Ginove
655, Boul. de la Montagne
Saint-Casimir, Qc, Canada
Goa 3L0
Tel.: (418) 339-2191
Fax.: (418) 339-2192

Distributors:



Tel.: (450) 619-0080

Fax: (866) 763-9409



Tel.: (800) 336-6637

Fax: (410) 355-7170